



AiM Infotech

Harness of 37 pins Deutsch connector + 2
thermocouples EVO5

Release 1.00



N.rev. / Rev. N.	Descrizione / Description	Data / date	Firma / Sign	Contr. da / Ckd. by																																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="7">Table of cables ending with 4 pins Binder 719 female connector</th> </tr> <tr> <th>37 pins Deutsch connector pin</th> <th>Cable colour</th> <th>Binder connector pin</th> <th>Cable type</th> <th>Length</th> <th>Channel</th> <th>Label</th> </tr> <tr> <td>30 31 32 33</td> <td>White Black Red Blue</td> <td>1 2 3 4</td> <td>4x0.35 mm²</td> <td>360 mm</td> <td>Analog channel 3 GND Vbattery Vreference</td> <td>Channel 3</td> </tr> <tr> <td>34 35 36 37</td> <td>White Black Red Blue</td> <td>1 2 3 4</td> <td>4x0.35 mm²</td> <td>360 mm</td> <td>Analog channel 4 GND Vbattery Vreference</td> <td>Channel 4</td> </tr> <tr> <td>19 20 21</td> <td>White Black Blue nc</td> <td>1 2 3 4</td> <td>3x0.35 mm²</td> <td>320 mm</td> <td>Speed 1 GND Vbattery nc</td> <td>Speed 1</td> </tr> <tr> <td>16 17 18</td> <td>nc Black Blue White</td> <td>1 2 3 4</td> <td>3x0.35 mm²</td> <td>320 mm</td> <td>nc GND Vbattery Optical lap</td> <td>Lap</td> </tr> <tr> <td>12 14 13</td> <td>White* Black Blue* nc</td> <td>1 2 3 4</td> <td>Twistato 2x0.35+1x0.35 mm²</td> <td>1100 mm</td> <td>USB D+ GND USB D- nc</td> <td>USB</td> </tr> </table>					Table of cables ending with 4 pins Binder 719 female connector							37 pins Deutsch connector pin	Cable colour	Binder connector pin	Cable type	Length	Channel	Label	30 31 32 33	White Black Red Blue	1 2 3 4	4x0.35 mm ²	360 mm	Analog channel 3 GND Vbattery Vreference	Channel 3	34 35 36 37	White Black Red Blue	1 2 3 4	4x0.35 mm ²	360 mm	Analog channel 4 GND Vbattery Vreference	Channel 4	19 20 21	White Black Blue nc	1 2 3 4	3x0.35 mm ²	320 mm	Speed 1 GND Vbattery nc	Speed 1	16 17 18	nc Black Blue White	1 2 3 4	3x0.35 mm ²	320 mm	nc GND Vbattery Optical lap	Lap	12 14 13	White* Black Blue* nc	1 2 3 4	Twistato 2x0.35+1x0.35 mm ²	1100 mm	USB D+ GND USB D- nc	USB
Table of cables ending with 4 pins Binder 719 female connector																																																					
37 pins Deutsch connector pin	Cable colour	Binder connector pin	Cable type	Length	Channel	Label																																															
30 31 32 33	White Black Red Blue	1 2 3 4	4x0.35 mm ²	360 mm	Analog channel 3 GND Vbattery Vreference	Channel 3																																															
34 35 36 37	White Black Red Blue	1 2 3 4	4x0.35 mm ²	360 mm	Analog channel 4 GND Vbattery Vreference	Channel 4																																															
19 20 21	White Black Blue nc	1 2 3 4	3x0.35 mm ²	320 mm	Speed 1 GND Vbattery nc	Speed 1																																															
16 17 18	nc Black Blue White	1 2 3 4	3x0.35 mm ²	320 mm	nc GND Vbattery Optical lap	Lap																																															
12 14 13	White* Black Blue* nc	1 2 3 4	Twistato 2x0.35+1x0.35 mm ²	1100 mm	USB D+ GND USB D- nc	USB																																															
* These two wires are twisted																																																					
Rif. / Ref.	Q.tà / Q.ty	Materiale / Material		N. articolo / Item N.																																																	
Progettato da / Designed by		Contr. da / Ckd. by	Approvato da / Approved by	Nome file / File name	Data / Date Scala / Scale																																																
			Titolo / Title Cavo del connettore Deutsch 37 pin con 2 termocoppie per EVO5																																																		
			N. disegno / Drawing N. 04.586.05	Rev. / Rev. Foglio / Sheet 2 of 3																																																	

N.rev. / Rev. N.	Descrizione / Description				Data / date	Firma / Sign	Contr. da / Ckd. by																												
<table border="1"> <tr> <th colspan="7">Table of cables ending with Mignon connectors</th> </tr> <tr> <th>37 pins Deutsch connector pin</th> <th>Cable colour</th> <th>Binder connector pin</th> <th>Cable type</th> <th>Length</th> <th>Channel</th> <th>Label</th> </tr> <tr> <td>22 23</td> <td>Yellow Red</td> <td>+ -</td> <td>compensated</td> <td>330 mm</td> <td>Analog channel 1 GND</td> <td>Channel 1</td> </tr> <tr> <td>26 27</td> <td>Yellow Red</td> <td>+ -</td> <td>compensated</td> <td>330 mm</td> <td>Analog channel 2 GND</td> <td>Channel 2</td> </tr> </table>								Table of cables ending with Mignon connectors							37 pins Deutsch connector pin	Cable colour	Binder connector pin	Cable type	Length	Channel	Label	22 23	Yellow Red	+ -	compensated	330 mm	Analog channel 1 GND	Channel 1	26 27	Yellow Red	+ -	compensated	330 mm	Analog channel 2 GND	Channel 2
Table of cables ending with Mignon connectors																																			
37 pins Deutsch connector pin	Cable colour	Binder connector pin	Cable type	Length	Channel	Label																													
22 23	Yellow Red	+ -	compensated	330 mm	Analog channel 1 GND	Channel 1																													
26 27	Yellow Red	+ -	compensated	330 mm	Analog channel 2 GND	Channel 2																													
<table border="1"> <tr> <th colspan="7">Table of cables ending with 5 pins Binder 712 female connector</th> </tr> <tr> <th>37 pins Deutsch connector</th> <th>Cable colour</th> <th>Binder connector pin</th> <th>Cable type</th> <th>Length</th> <th>Chanel</th> <th>Label</th> </tr> <tr> <td>3 4 5 6 7</td> <td>White Black Red Blue Orange</td> <td>1 2 3 4 5</td> <td>5x0.25 mm²</td> <td>350 mm</td> <td>CAN+ exp GND Vbattery CAN- exp Vbext</td> <td>Exp.</td> </tr> </table>								Table of cables ending with 5 pins Binder 712 female connector							37 pins Deutsch connector	Cable colour	Binder connector pin	Cable type	Length	Chanel	Label	3 4 5 6 7	White Black Red Blue Orange	1 2 3 4 5	5x0.25 mm ²	350 mm	CAN+ exp GND Vbattery CAN- exp Vbext	Exp.							
Table of cables ending with 5 pins Binder 712 female connector																																			
37 pins Deutsch connector	Cable colour	Binder connector pin	Cable type	Length	Chanel	Label																													
3 4 5 6 7	White Black Red Blue Orange	1 2 3 4 5	5x0.25 mm ²	350 mm	CAN+ exp GND Vbattery CAN- exp Vbext	Exp.																													
<table border="1"> <tr> <th colspan="5">Table of not cabled cables</th> </tr> <tr> <th>37 pins Deutsch connector</th> <th>Cable colour</th> <th>Cable type</th> <th>Length</th> <th>Label</th> </tr> <tr> <td>15</td> <td>Bianco</td> <td>1x0.5 mm²</td> <td>550 mm</td> <td>RPM</td> </tr> <tr> <td>2 1</td> <td>Nero Rosso</td> <td>1x0.5 mm² 1x0.5 mm²</td> <td>550 mm</td> <td>GND 9-15 Power input</td> </tr> <tr> <td>8 9 10 11</td> <td>Bianco Blu Nero Blu</td> <td>1x0.5 mm² 1x0.5 mm² 1x0.5 mm² 1x0.5 mm²</td> <td>550 mm</td> <td>CAN 1+ CAN1- K line GND K line</td> </tr> </table>								Table of not cabled cables					37 pins Deutsch connector	Cable colour	Cable type	Length	Label	15	Bianco	1x0.5 mm ²	550 mm	RPM	2 1	Nero Rosso	1x0.5 mm ² 1x0.5 mm ²	550 mm	GND 9-15 Power input	8 9 10 11	Bianco Blu Nero Blu	1x0.5 mm ² 1x0.5 mm ² 1x0.5 mm ² 1x0.5 mm ²	550 mm	CAN 1+ CAN1- K line GND K line			
Table of not cabled cables																																			
37 pins Deutsch connector	Cable colour	Cable type	Length	Label																															
15	Bianco	1x0.5 mm ²	550 mm	RPM																															
2 1	Nero Rosso	1x0.5 mm ² 1x0.5 mm ²	550 mm	GND 9-15 Power input																															
8 9 10 11	Bianco Blu Nero Blu	1x0.5 mm ² 1x0.5 mm ² 1x0.5 mm ² 1x0.5 mm ²	550 mm	CAN 1+ CAN1- K line GND K line																															
Rif. / Ref.	Q.tà / Q.ty	Materiale / Material			N. articolo / Item N.																														
Progettato da / Designed by		Contr. da / Ckd. by	Approvato da / Approved by	Nome file / File name		Data / Date	Scala / Scale																												
			Titolo / Title																																
			Cavo del connettore Deutsch 37 pin con 2 termocoppie per EVO5																																
N. disegno / Drawing N.			04.586.05		Rev. / Rev.	Foglio / Sheet																													
						3 of 3																													